

Ordering Code:

Job Name:		Contact:
	_	
	r	



smoky metal

Matrix Ceiling Mount

Description

Fixture Type:

Bruck's European and American Artisan, mouth-blown glass is known throughout the world for its quality and beauty. Several light source options, colors and finishes allow for a unique design. Most of Bruck's glass allows for easy screw-on / screw-off for a simple installation. The Matrix Ceiling Mount includes a 4" ceiling mount canopy. Dimmable with ELV (Reverse Phase) at 120V only to 10%.

Mounting

Round canopy over a 4" recessed round j-box.

Ordering Codes

Follow the steps to specify your fixture, example: 100 - 905 - mc - CM

Part Number	Shade Color	Finish	Mounting
104 400 lm LED	905 smoky metal	bz bronze	CM 4" ceiling canopy
100 low voltage		ch chrome	
		mc matte chrome	



Light

echnical	Specs		
nt Source	104 - 400 lm LED Canopy	100 - Low Voltage Bi-pin Canopy	
LED CCT SDCM CRI Ra Life	Cree XTE 2800K 3 MacAdam Ellipse 90 min Based on IESNA-LM80-2008: 90% of initial lumens after 65,500 hrs	lamp dependent	
Socket Listing	Integrated LED module ETLus Listed to UL1598, UL1574 and UL2108 (Suitable for dry locations only) CETL Listed to CSA C22.2 #250.0 and #9.0	GY6.35 socket ETLus Listed to UL1598, UL1574 and UL2108 (Suitable for dry locations only) CETL Listed to CSA C22.2 #250.0 and #9.0	
Canopy	100-277VAC, 50/60Hz input 8W, 8VA Dimmable: ELV (Reverse Phase) Mount to 3 1/2" - 4" round J-Box Short circuit protection Thermal protection	120VAC 50/60Hz input 11.7V AC output 49W, 50VA (max 50W lamp) Mount to 3 1/2" - 4" round J-Box Short circuit protection Overload protection Thermal protection	
Warranty	3 year limited fixture warranty	1 year limited fixture warranty	





Made in the USA - meets the requirements of the Buy American provision within the ARRA