



**Fluorescent Spiro** / MEDIUM SUSPENSION  
by Remedios Simón



REF. SPRO SM W 28  
Spiro Medium



References

- SPRO SM W  
SPRO SM BK  
SPRO SM 21  
SPRO SM 26
- SPRO SM W DIM  
SPRO SM BK DIM  
SPRO SM 21 DIM  
SPRO SM 26 DIM
- SPRO SM W DIMRC  
SPRO SM BK DIMRC  
SPRO SM 21 DIMRC  
SPRO SM 26 DIMRC

Awards



Shade / Wood Outer Shell

- Opaque Wood Outer shell \***
- 21 Natural Cherry
  - 26 Red tulip poplar

Spiral colours \*

- 21 Natural Cherry
- 26 Red

\* Additional colours available on request.

Certificates



Class I  
220 - 250V

Shade / Acrylic Outer Shell

- Opaque Acrylic Outer shell**
- W Matt White
  - BK Matt Black

Spiral colours

- 20 Ivory White
- 21 Natural Cherry
- 22 Natural Beech
- 24 Yellow
- 25 Orange
- 26 Red
- 28 Blue
- 29 Grey
- 30 Turquoise
- 31 Chocolate
- 32 Pink

Components



**Top diffuser**  
Black or White

**Note:** The standard top diffuser is white. Black is also available if you want no upward light diffusion.

**Bottom diffuser**  
Transparent acrylic




**Metal canopy**  
Brushed Nickel  
ø 10 cm - disc ø 14 cm

**Electrical cable**  
Transparent 2 m drop



**Steel cable**  
4 x 2 m drop



**Box size**  
95 x 92 x 48 cm  
Wood crated for transport

**Box volume**  
0,42m<sup>3</sup>

**Weight**  
Gross - 40,9 Kg | W - BK  
Net - 9,6 Kg  
Gross - 40 Kg | 21 - 26  
Net - 8,3 Kg



**T5**  
  
Linear Fluorescent  
4 x 24 W  
(included)

**Energy class**

	Tube included



**Ballast**

- TRIDONIC  
1 unit - Ref. 22185212
- TRIDONIC  
1 unit - Ref. 22176210
- BAG  
2 units - Ref. 10097296  
+ Remote Control - DANLERS

Details

Input Voltage	Luminous Flux *	CRI	Watt.	Total Watt.	CCT	Lifetime (L70)
220 - 250V	1690 lm <sup>(1)</sup> 697 lm <sup>(2)</sup>	85	4 x 24 W	96 W	3000 K	30000h

\* (1) Measurements taken using matt white outer shell and white shades, Veneer Ref: 20 Ivory White  
(2) Measurements taken using matt white outer shell and white shades, Veneer Ref: 21 Natural Cherry