



SP ULA 160
Design by Timo Ripatti

Collection consisting of wall lamps, ceiling lamps and suspended lamps in aluminium.
Available in several colours and sizes.

Typology: SUSPENDED LAMP

Ratings


- Built in **LED** module
- CCT 3000 K
- Downlight or uplight
- Surface installation over holes
- Supply voltage ~100-240VAC
- Switch mode: on-off
- Dimmable 1-10V LED driver
- Painted aluminium profile 23 x 23 mm
- Opalescent diffuser

Product code composition

kg 9,1 m³ 0.57

U-LIGHT / suspension with canopy / DRIVER INCLUDED

Type	Article	Colours	Version	Source
SP	ULA 160 LED	AN anthracite grey	XX standard canopy	LED 125W - diffused beam 3000K
		RU rust brown		



rosone standard / standard canopy



CE IP20 CRI90 **LED** ~9900 lm 79 lm/W 100-240Vac

example composition code | SP | ULA160LED | AN | XX |

Available colors



AN
Anthracite
grey



RU
Rust brown

EELc (Energy Efficiency Label compatibility) contain built in LED lamps that cannot be changed: A, A+, A++

CUSTOMER _____ NOTES _____

SPULA160LED _ _ XX

Luminous flux (lm) and efficacy (lm/W) for all built-in LED luminaires is estimated based on nominal ratings of the LED sources.
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.