U-LIGHT - SP ULA 160 - recessed - technical sheet





SPULA160 - recessed Design by Timo Ripatti

Collection consisting of wall lamps, ceiling lamps and suspended lamps in aluminium.


Available in several colours and sizes.

Typology: SUSPENDED LAMP

Ratings

- Built in IED module
- •CCT 3000 K
- Downlight or uplight
- •Surface installation over holes (cable grippers) and in ceiling cut-out (recessed canopy)
- •Supply voltage 24VDC
- Switch mode: on-off
- •Painted aluminium profile 23 x 23 mm
- Opalescent diffuser

kg 4,8 m³ 0.57



rosone incasso / recessed canopy





Product code composition

U-LIGHT / recessed suspension lamp / DRIVER NOT INCLUDED

Туре	Article	Colours		Version		Source	
SP	ULA 160 LED	AN	anthracite grey	IN	recessed canopy	LED	102W - diffused beam 3000K - 24Vpc
		RU	rust brown				

CE IP20 CRI90 deficiated FSU ~9900 lm 97 lm/W 24

foro - hole Ø 4,5 cm / profondità min - min depth 10 cm

example composition code | SP | ULA160LED | RU | IN

for optional drivers or dimming technology please refer to our pricelist or contact our representatives

Available colors







RU Rust brown

EELc (Energy Efficiency Label compatibility) contain built in LED lamps that cannot be changed: A, A+, A++

CUSTOMER

NOTES

SPULA160LED _ _ IN

Luminous flux (lm) and efficacy (lm/W) for all built-in LED luminaires is estimated based on nominal ratings of the LED sources. Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.