

STUDIO SPOT TRACE 3/70 alu pol/black 2700 K
SP50-8



TECHNICAL SPECIFICATIONS

| | |
|------------------------------------|---------------------------|
| Lamp holder | LED |
| Mounting method | ceiling-mounted (surface) |
| Light emission | direct |
| Light distribution | symmetric |
| Luminaire luminous flux | 3x 650 lm |
| Colour temperature | 2700 K |
| Colour rendering index (CRI) | > 90 |
| White impression | warm white |
| Rated voltage (range) | 220-240 V |
| Power frequency | 50/60 Hz |
| Power consumption (maximum) | 3x 16 W |
| Surface | polished |
| Colour of covering | black |
| Housing material | aluminium |
| Type of lamp control gear | Driver |
| Ballast included | Yes |
| Protection class | II |
| Connection cable (number of cores) | 3 |
| Number of lampheads | 3 |
| Energy efficiency | A - A++ |
| Dimmable | Yes |
| Type of Dimmer | phase rotary dimmer |
| Material of the cover | plastic |
| Length | 700 mm |
| Width | 45 mm |
| Height | 135+45 (Schiene) = 180 mm |
| Head adjustable | Yes |
| lamphead is rotatable | Yes |
| | glossy |
| | aluminium |