# **NELLY** – PL UKIYO G – technical sheet





### **PLUKIYOG**


### Design by Manuel Vivian

Collection consisting of ceiling or wall lamps with metal frame and white removable, washable elastic mesh fabric covering. Available in several sizes. Screw fitting light source.

Typology: CEILING-WALL LAMP

#### Ratings

- •E27
- Diffused
- •Surface installation over holes
- •Supply voltage ~220-240V
- •Switch mode: on-off
- Steel frame, painted



Fireproof covering composed of two overlapping elastic fabrics
Net composition: 80% polyamide, 20% elastane (spandex)
Fabric composition: 67% polyamide, 33% elastane (spandex)
Weight 405 gr/m²
Glow wire 750°C

Product code composition

UKIYO / tessuto INCLUSO - applicazione a soffitto o a parete / fabric INCLUDED - application: both as ceiling or wall lamp Colours Article Finish Source Type PL **UKIYO G** BC white XX white E27 3 x Max 16W LED or 3 x Max 70W halo metal  $\epsilon$ IP20 +LED example composition code | PL | UKIYOG BC XX E27

for additional fabric please refer to our pricelist or contact our representatives

## Available lampshade colors



BC White

EELc (Energy Efficiency Label compatibility): E, D, C, B, A, A+, A++

PLUKIYOGBC XXE27

CUSTOMER

**NOTES** 

Luminous flux (lm) and efficacy (lm/W) for all LED luminaires is estimated based on nominal ratings of the LED sources. Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.