



PLURBMIG
Design by Dima Loginoff

Collection consisting of aluminium ceiling lamps and suspended lamps.
Available in several colours and sizes Built-in dimmable


Typology: CEILING

Ratings

- Built in line voltage **LED** module
- CCT 3000 K
- Downlight
- Surface installation over holes
- Supply voltage ~220-240V
- Switch mode: on-off, dimmable trailing edge
- Aluminium body, painted
- Diffuser

Product code composition

URBAN MINI



Type	Article	Colours	Finishing	Source
PL	URB MI G	BC wrinkled white BR matt bronze NI matt nickel	XX	LED 8W - diffused beam 3000K*, 2700K, 4000K

IP20 CRI90 220-240V_{AC} **LED** ~560 lm* 70 lm/W*
 example composition code **PL URBMIG BR XX LED**

Available colors



BC
Wrinkled
white

BR
Matt
bronze

NI
Matt
nickel

EELc (Energy Efficiency Label compatibility) contain built in LED lamps that cannot be changed: A, A+, A++

CUSTOMER _____ NOTES _____

PLURBMIG _ _ XXLED

NOTICE:

Luminous flux (lm) and efficacy (lm/W) for all LED luminaires is based on nominal ratings of the LED sources.
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.