






The Balke is easy to carry about, bringing light to wherever you need it. This model is basically a compact and easy-to-handle version of the emblematic Sammode tubular luminaire. This sturdy light is great for both indoor and outdoor areas. Hang the luminaire on pattresses to light up the kitchen or on a tree branch to illuminate those summer meals on the patio.



Balke

Portable Light



Balke

Structure	Reflector	Designation	Code
● Coal	● Copper	BALKE 100 B2C COAL COAL GR C 520 BPI CL1 PY MR P1	80145118
	● Brass	BALKE 100 B2C COAL COAL GR B 520 BPI CL1 PY MR P1	80145119
	● Petrol	BALKE 100 B2C COAL COAL GR P 520 BPI CL1 PY MR P1	80145120
● Marsala	● Silver	BALKE 100 B2C MARS MARS GR S 520 BPI CL1 PY MR P1	80145121
○ White	● Brass	BALKE 100 B2C WHITE WHITE GR B 520 BPI CL1 PY MR P1	80145122

Accessories

To be ordered separately



E14 LED filament lamp 4W
2700K clear

17500002



Wall-mount pattress
COAL
MARSALA
WHITE

17500411
17500412
17500413



Balke

Portable Light



Specification



Technical characteristics

Light source	2 E14 lamps, 11W max, not included
Lighting comfort	Flux-breaker grid
Dimming	By built-in dimming button
Supply voltage	220-240V 50/60Hz
Electrical class	Class I
Operating temperature	-20°C to +30°C

Easy intallation and maintenance

Connection	Provided with 4 m 5G1,5 cable with tinned copper meshwork under transparent tubing with a european plug IP44
Mounting	Supplied with a wall-mount pattress
Maintenance	Maintenance by releasing the 2 closing screws, removing the end cap and extracting the gear tray

Materials

Structure	Powder-coated aluminium with anti-corrosion treatment for outdoor use
Louvre	Stainless steel grid
Housing	Borosilicate-glass diffuser for inside/outside use
End caps and fixing straps	316L stainless steel

Standards

Waterproofness	IP66, IP68
Resistance to IK shocks	IK07
Fire resistance	Non-flammable