Lotus Seed Right

REFERENCE AP1474/5/R



DESCRIPTION

Inspired by an entangled blooming lotus, the design follows the inherent evolutionary disposition of an organism, proposing a spiral arrangement almost like a living sculpture of motion and growing light sources. The egg-shaped glass pieces emit light to involve the entire piece as a single organic silhouette, a Serip feature throughout all lighting designs, revealing an interesting glass work that includes bubbles in each piece - factor that confers unique characteristics to the light emission.


Designed and produced by hand in Portugal.

Serip reserves the right to make changes or improvements at any time it deems useful to guarantee the highest quality standards for its products.

Hand-finished, some variations may occur.

All the glass models are designed by Serip and exclusively handmade produced, establishing a unique and prestigious feature of the glass handwork art. For this reason, there is the possibility of variation in measures, weight, colour and shape represented.

TECHNICAL DRAWING



TECHNICAL SPECIFICATIONS

MEASUREMENTS

FIXTURE SIZE & WEIGHT Width 50.00cm / 20.00in Height 80.00cm / 31.00in **Depth** 20.00cm / 8.00in Weight 8.00kg / 18.00lb

PACKAGE SIZE & WEIGHT (m)Package 1/2 0.64m x 0.86m x 0.64m =0.35CBM (in)Package 1/2 0.25in x 0.34in x 0.25in

ELECTRIC FEATURE

IP degree IP 20


220-240V 50Hz-60Hz Max Power Consuption 30W **Light Sources** 5 x G9 Max 6W

Included Sources Light Sources 5 x G9 LED 2W **CRI** 80

Light Sources 5 x G9 LED 3W Kelvin 3000 **CRI** 80

Max Power Consuption 30W **Light Sources** 5 x G9 Max 6W

CARE INSTRUCTIONS



Always avoid the use of harsh chemicals or abrasive cleaners as they may cause damage to the fixture's finish.

Cleaning is limited to the outer surfaces, shades or glass. It is important to ensure that no moisture enters the terminal compartment or reaches any live parts.

As our products are subject to technical modifications, we cannot guarantee, that all information is always up to date. Please contact our technical department with any queries.

Installation Ceilling

F

This luminaire allows lights sources with energy

ENERGY RATING

efficiency class

Lumens 1150lm

Kelvin 3000

Optional Sources Lumens 1500lm

110-120V 50Hz-60hZ

=12.40ft³

CERTIFICATIONS









OPTIONAL FINISHES

GLASS FINISHES



Clear (10)

METAL FINISHES



Copper Silver (FP) Silver/White Lead (CH) Palladium Black (PR) Gold/White Gold (FO) (CO) Patina (PL) Patina (FO/PB)



Talha (TA)