## WIREFLOW

Design by Arik Levy.



Reference

0308.

Application

Hanging lamps

Installation type

Surface

## Description

Wireflow designed by Arik Levy. A hanging lamp which reviews and updates the chandelier look through an exercise of simplification that explores its essence and enhances its outline with great delicacy and at the same time a strong formal presence. Its appearance, as a structure of fine cables finished with eight LED terminals, discretely connects with classic chandelier models, taking this type of lamp to a new, groundbreaking and futuristic dimension. Employing CREA product configurator software, the design can be modified to adapt to your specific project requirements.

Diffuser

Pressed-glass diffuser

Materials


Diffuser: Glass Body: Aluminum Horizontal rods: Steel Ceiling rose: Steel

Finish



0308-04 Black lacquer (RAL 9005)

Sketch



**Electrical characteristics** 

6 x LED 4.5W 350mA



Total 26.9 W





Led 2700K CRI >80 2942 lm 109 lm/W

Fixture: 1180 lm 60 lm/W

Driver included: CC - Constant Current 350 mA 100-240V 50/60Hz

Electronic dimming DALI 1-10V PUSH

ficha.fichatecnicaproducto.regulacion.opcional SMART

**Physical characteristics** 

2 Box / 0.27 x 0.60 x 0.60 m. / Vol. 0.1238  $\ensuremath{\text{m}}^3$  / Gross weight 8.4 kg. / Net weight 7.6 kg.

Installation and assembly

Please, see the installation manual

**Light distribution** 

## **General lighting**

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Efficiency: 40.11% Isolux: Floor Coordinate system : CG Light position:

Total flux: 2941.60 X=0.00m Y=0.00m Z=2.50m

Maximum value: 53.87 Light position: C=15.00 G=55.00 Symmetry on the planes: Double symmetrical

