WIREFLOW

Design by Arik Levy.

VIBIA

Reference

0313.

Application Hanging lamps

Installation type Surface

Description

Wireflow designed by Arik Levy. A hanging lamp which reviews and updates the chandelier look through an exercise of simplification that explores its essence and enhances its outline with great delicacy and at the same time a strong formal presence. Its appearance, as a structure of fine cables finished with eight LED terminals, discretely connects with classic chandelier models, taking this type of lamp to a new, groundbreaking and futuristic dimension. Employing CREA product configurator software, the design can be modified to adapt to your specific project requirements.

Diffuser


Pressed-glass diffuser

Materials Diffuser: Glass Body: Aluminum Horizontal rods: Steel Ceiling rose: Steel



0313-04 Black lacquer (RAL 9005)

Sketch





A⁺

Electrical characteristics

Total 17.9 W





Led 2700K CRI >80 1961 lm 109 lm/W Fixture: 787 lm 60 lm/W Driver included: CC - Constant Current 350 mA 100-240V 50/60Hz

Electronic dimming DALI 1-10V PUSH ficha.fichatecnicaproducto.regulacion.opcional SMART

Physical characteristics

2 Box / 0.27 x 0.60 x 0.60 m. / Vol. 0.1238 m³ / Gross weight 7.4 kg. / Net weight 6.7 kg.

Installation and assembly Please, see the installation manual

Light distribution

General lighting


Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Efficiency : 40.11% Coordinate system : CG Total flux : 1961 Maximum value : 53.86 Light position : C=15.00 G=55.00

Isolux : Floor Light position : X=0.00m Y=0.00m Z=2.50m



VIBIA LIGHTING, S.L.U. Barcelona, 72 - 74. 08820 El Prat de Llobregat (Barcelona - Spain). Tel 934 796 970. Fax 934 796 973. vibia@vibia.com www.vibia.com



VIBIA LIGHTING, S.L.U. Barcelona, 72 - 74. 08820 El Prat de Llobregat (Barcelona - Spain). Tel 934 796 970. Fax 934 796 973. vibia@vibia.com www.vibia.com