WIREFLOW

Design by Arik Levy.



Reference

0320.

Application

Hanging lamps

Installation type

Surface / Built-in

Description

Wireflow designed by Arik Levy. Linear hanging lamp Its appearance, as a structure of fine cables finished with two 4,5W LED terminals, is ideal for discretely connecting with classic chandelier models, taking this type of lamp to a new, groundbreaking and futuristic dimension. Employing CREA product configurator software, the design can be modified to adapt to your specific project requirements. Ideal for decorating large spaces, particularly ones with high ceilings, including hotel reception areas, retail sales points and food and drinks bars.

Materials


Body: Aluminum Horizontal rods: Steel Ceiling rose: Aluminum Diffuser: Polycarbonate

Finish



0320-04 Black lacquer (RAL 9005)

Sketch



Electrical characteristics

2 x LED 4,5W 350mA

Total 9.0 W







Led 2700K CRI >80 981 lm 109 lm/W

Fixture: 453 lm 70 lm/W

Driver included: CC - Constant Current 350 mA 110-240V 50/60Hz

Electronic dimming 1-10V PUSH

 $\textbf{ficha.fichatecnica} producto.regulacion.opcional \ \mathsf{DALI}$

Technical characteristics

- Linear canopy

Physical characteristics

1 Box / $0.08 \times 0.20 \times 0.70 \text{ m.}$ / Vol. 0.0105 m^3 / Gross weight 3.1 kg. / Net weight 2.6 kg.

Installation and assembly

Please, see the installation manual

Light distribution

Highlight

Lamp used to highlight a specific element.



Photometric data

Efficiency: 46.23% Coordinate system : CG Total flux: 980.60

Light position: X=0.00m Y=0.00m Z=2.50m Maximum value: 320.25

Light position: C=0.00 G=0.00 Symmetry on the planes: Double symmetrical

×













Isolux: Floor

