WIREFLOW

Design by Arik Levy.



Reference

0401.

Application

Hanging lamps

Installation type

Surface

Description

Wireflow designed by Arik Levy. A hanging lamp which reviews and updates the chandelier look through an exercise of simplification that explores its essence and enhances its outline with great delicacy and at the same time a strong formal presence. Its appearance, as a structure of fine cables finished with eight LED terminals, discretely connects with classic chandelier models, taking this type of lamp to a new, groundbreaking and futuristic dimension. Employing CREA product configurator software, the design can be modified to adapt to your specific project requirements.

Materials


Diffuser: Polycarbonate Body: Aluminum Horizontal rods: Steel Ceiling rose: Steel

Finish



0401-04 Black lacquer (RAL 9005)

Sketch



Electrical characteristics

8 x LED 4,5W 350mA

Total 35.8 W

A⁺



Led 2700K CRI >80 3922 lm 109 lm/W

Fixture: 1813 lm 0 lm/W

Driver included: CC - Constant Current 350 mA 100-240V 50/60Hz

Electronic dimming DALI 1-10V PUSH

ficha.fichatecnicaproducto.regulacion.opcional SMART

Physical characteristics

 $2\; Box\, /\, 0.09\; x\; 1.16\; x\; 1.13\; m.\; /\, Vol.\; 0.2100\; m^3\, /\,$ Gross weight 15.0 kg. / Net weight 13.1 kg.

Installation and assembly

Please, see the installation manual

Light distribution

Highlight

Lamp used to highlight a specific element.



Photometric data

Efficiency: 46.23% Isolux: Floor Coordinate system : CG Light position :

Total flux: 3922.20 X=0.00m Y=0.00m Z=2.50m

Maximum value: 320.25 Light position: C=0.00 G=0.00

Symmetry on the planes: Double symmetrical

Certificates











