## WIREFLOW

Design by Arik Levy.



Reference

0403.

Application

Hanging lamps

Installation type

Surface

## Description

Wireflow designed by Arik Levy. A hanging lamp which reviews and updates the chandelier look through an exercise of simplification that explores its essence and enhances its outline with great delicacy and at the same time a strong formal presence. Its appearance, as a structure of fine cables finished with eight LED terminals, discretely connects with classic chandelier models, taking this type of lamp to a new, groundbreaking and futuristic dimension. Employing CREA product configurator software, the design can be modified to adapt to your specific project requirements.

Materials


Diffuser: Polycarbonate Body: Aluminum Horizontal rods: Steel Ceiling rose: Steel

Finish



0403-04 Black lacquer (RAL 9005)

Sketch



**Electrical characteristics** 

8 x LED 4,5W 350mA

Total 35.8 W





Led 2700K CRI >80 3922 lm 109 lm/W

**Fixture:** 1813 lm 0 lm/W

Driver included: CC - Constant Current 350 mA 100-240V 50/60Hz

Electronic dimming DALI 1-10V PUSH

ficha.fichatecnicaproducto.regulacion.opcional SMART

**Physical characteristics** 

2 Box / 0.27 x 0.60 x 0.60 m. / Vol. 0.1558  $\ensuremath{\text{m}}^3$  / Gross weight 12.5 kg. / Net weight 11.3 kg.

Installation and assembly

Please, see the installation manual

**Light distribution** 

## Highlight

Lamp used to highlight a specific element.



Photometric data

Efficiency: 46.23% Isolux: Floor Coordinate system : CG Light position :

Total flux: 3922.20 X=0.00m Y=0.00m Z=2.50m

Maximum value: 320.25 Light position: C=0.00 G=0.00

Symmetry on the planes: Double symmetrical

Certificates











