BIG

Design by Lievore Altherr Molina.



Reference

0530.

Application

Ceiling Lamps

Installation type

Surface

Description

Accessible ceiling light for indoor use, designed by Lievore, Altherr, Molina. Direct, diffuse and uniform light distribution. Chrome or matt white lacquer body and white opal methacrylate diffuser. Its large size makes it ideal for lighting large spaces from a single point.

Diffuser

Methacrylate diffuser

Materials

Shade: Methacrylate Ring: Steel


Finish



0530-01 Chrome (Metallic finish)



Sketch



Electrical characteristics

2 x 2G11 230V 36W

AND

2 x 2G11 230V 24W 0-0Total 120.0 W







Fixture: 5533 lm 46 lm/W

Driver included: CV - Contant Voltage 230V 50Hz

Electronic dimming DALI PUSH

Technical characteristics

- Dimmable electronic ballast DALI System and Push.
- Easy-to-install and replace bulb system

Physical characteristics

1 Box / 0.38 x 1.37 x 1.37 m. / Vol. 0.7080 m³ / Gross weight 21.0 kg. / Net weight 18.9 kg.

Installation and assembly

Please, see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.




Photometric data

Efficiency: 58.86% Isolux: Floor Coordinate system : CG Light position : X=0.00m Y=0.00m Z=3.00m Total flux : 9400.00 lm

Maximum value : 210.42 cd/klm Light position: C=0.00 G=0.00

Symmetry on the planes : Double symmetrical



Certificates







