BIG

Design by Lievore Altherr Molina.



Reference

0535.

Application

Hanging lamps

Installation type

Surface

Description

Hanging lamp for indoor use, designed by Lievore, Altherr, Molina. Direct, diffuse and uniform light distribution. Chrome or matt white lacquer body and white opal methacrylate diffuser with an opaque shade which therefore projects more light downwards.

Diffuser

Methacrylate diffuser

Materials

Shade: Methacrylate Ring: Steel


Finish



0535-01 Chrome (RAL 9016)



Sketch



Electrical characteristics

2 x 2G11 230V 36W AND

2 x 2G11 230V 24W

Total 120.0 W







Fixture: 5533 lm 46 lm/W

Driver included: CV - Contant Voltage 230V 50Hz

Electronic dimming DALI PUSH

Technical characteristics

- Dimmable electronic ballast DALI System and Push.
- Easy-to-install and replace bulb system

Physical characteristics

1 Box / 0.38 x 1.37 x 1.37 m. / Vol. 0.7080 m³ / Gross weight 25.6 kg. / Net weight 23.0 kg.

Installation and assembly

Please, see the installation manual

Light distribution

General lighting - opaque shade

Lamp for general lighting with an opaque shade and distributing light upwards and/or downwards mainly.




Photometric data

Efficiency: 58.86% Isolux: Floor Coordinate system : CG Light position : X=0.00m Y=0.00m Z=3.00m

Total flux : 9400.00 lm Maximum value: 210.42 cd/klm Light position: C=0.00 G=0.00

Symmetry on the planes : Double symmetrical



Certificates







