PLUS

Design by X. Claramunt and M. de Mas.

Reference

0621.

Application

Ceiling Lamps

Installation type

Surface

Description

Asymmetrical ceiling light, designed by X. Claramunt and M. de Mas. Direct, diffuse and uniform light distribution. Convex methacrylate diffuser and matt white lacquer finish, though the whole fixture can be painted in the desired colour to make it blend perfectly into the ceiling. Its form recalls a real skylight.

Diffuser

Methacrylate diffuser

Materials

Body: Polyurethane foam
Diffuser: Methacrylate

Finish

0621-03 Matt white lacquer (RAL 9010)

Sketch



Electrical characteristics

4 x G5 230V 24W (T5) Total 96.0 W

A

Fixture: 1971 lm 21 lm/W
Driver included: CV - Contant Voltage 230V 50Hz

Electronic dimming DALI PUSH

Technical characteristics

- Easy-to-install and replace bulb system

Physical characteristics

1 Box / 0.45 x 0.95 x 0.95 m. / Vol. 0.4151 m³ /
Gross weight 16.9 kg. / Net weight 15.2 kg.

Installation and assembly

Please, see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Efficiency : 28.16%
Coordinate system : CG
Total flux : 7000.00 lm
Maximum value : 92.16 cd/klm
Light position : C=90.00 G=10.00
Symmetry on the planes : Symmetrical planes
270-90

Isolux : Floor
Light position :
X=0.00 Y=0.00 Z=3.00



Certificates

VIBIA LIGHTING, S.L.U. Barcelona, 72 - 74. 08820 El Prat de Llobregat (Barcelona - Spain). Tel 934 796 970. Fax 934 796 973.
vibia@vibia.com www.vibia.com

VIBIA LIGHTING, S.L.U. Barcelona, 72 - 74. 08820 El Prat de Llobregat (Barcelona - Spain). Tel 934 796 970. Fax 934 796 973.
vibia@vibia.com www.vibia.com