PLUS Design by X. Claramunt and M. de Mas.

VIBIA

Reference

0626.

Application Ceiling Lamps

Installation type Surface

Description

Symmetrical ceiling light, designed by X. Claramunt and M. de Mas. Direct, diffuse and uniform light distribution. Convex methacrylate diffuser and matt white lacquer finish, though the whole fixture can be painted in the desired colour to make it blend perfectly into the ceiling. Its form recalls a real skylight.

Diffuser


Methacrylate diffuser

Materials Body: Polyurethane foam Diffuser: Methacrylate

Finish

0626-03 Matt white lacquer (RAL 9010)

Sketch



Electrical characteristics 4 x G5 230V 24W (T5)

 $|\mathbf{A}\rangle$





Fixture: 1971 lm 21 lm/W Driver included: CV - Contant Voltage 230V 50Hz

Electronic dimming DALI PUSH

Technical characteristics

- Easy-to-install and replace bulb system

Physical characteristics

1 Box / 0.27 x 0.96 x 0.96 m. / Vol. 0.2488 m³ / Gross weight 15.1 kg. / Net weight 13.6 kg.

Installation and assembly

Please, see the installation manual

Light distribution


General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Efficiency : 28.62% Coordinate system : CG Total flux : 7000.00 lm Maximum value : 96.08 cd/klm Light position : C=0.00 G=0.00 Isolux : Floor Light position : X=0.00m Y=0.00m Z=3.00m



Certificates



VIBIA LIGHTING, S.L.U. Barcelona, 72 - 74. 08820 El Prat de Llobregat (Barcelona - Spain). Tel 934 796 970. Fax 934 796 973. vibia@vibia.com www.vibia.com

Total 96.0 W