QUADRA ICE

Design by Proli Diffusion Studio.



Reference

1132.

Application

Ceiling Lamps

Installation type

Surface

Description

Large ceiling lamp, in optical glass to fit perfectly into the setting as it has no profile. Cold light.

Diffuser

Optical-glass diffuser


Materials Diffuser: Glass


Finish



1132-00 White glass (RAL 9016)

Sketch





Electrical characteristics

1 x 2GX13 230V 22W (T5C)

1 x 2GX13 230V 40W (T5C)



Total 62.0 W



Fixture: 2339 lm 38 lm/W

Driver included: CV - Contant Voltage 230V 50Hz

Physical characteristics

1 Box / 0.27 x 0.76 x 0.76 m. / Vol. 0.1559 m³ / Gross weight 8.8 kg. / Net weight 7.9 kg.

Installation and assembly

Please, see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.




Photometric data

Efficiency: 64.98% Isolux : Floor ${\it Coordinate \ system: CG}$ Light position :

Total flux : 3600.00 lm X=0.00m Y=0.00m Z=3.00m

Maximum value : 176.94 cd/klm Light position: C=0.00 G=0.00

Symmetry on the planes : Double symmetrical



Certificates







