GUISE

Design by Stefan Diez.



Reference

2260.

Application

Wall Lamps

Installation type

Surface

Description

Vibia presents a wall lamp that integrates the LED light with the glass and making it pass through in such a way that it becomes invisible and then allowing it to appear out of nowhere.

Diffuser

Difusor de vidrio borosilicato transparente

Materials


Profile: Aluminum Diffuser: Borosilicate glass

Finish



2260-18 Matt graphite lacquer (ADAPTA RF 9913 WX)

Sketch



Electrical characteristics





Led 3000K CRI >90 871 Im 87 Im/W Fixture: 445.29 lm 41.23 lm/W

Driver included: CC - Constant Current 100-240V 50/60Hz

Electronic dimming OPTICAL SENSOR

Technical characteristics

- The glass is made of borosilicate. It is typical for the glass to have small air bubbles, some inclusions and tiny scratches. These do not affect the quality or the resistance of the glass.

Physical characteristics

1 Box / $0.00 \times 0.00 \times 0.00 \text{ m.}$ / Vol. 0.0428 m^3 / Gross weight 7.0 kg. / Net weight 4.0 kg.

Installation and assembly

Please, see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Efficiency: 1 ${\it Coordinate \ system: CG}$ Total flux: 445.29 lm

Light position: X=0.00ft Y=0.00ft Z=8.20ft Maximum value : 188.65 cd/klm

Certificates





Light position: C=0.00 G=85.00









Isolux: Isolux (Floor)

