

PALMA

Design by Antoni Arola.

Reference

3706.

Application

Wall Fixtures

Installation type

Surface mounted

Description

Vibia presents a horizontal wall lamp. It is expressed in a different way to the classical globe, new horizontal relationships at a large scale combined with vegetation.

Diffuser

Matte triplex opal blown-glass diffuser

Materials

Profile: Aluminum

Diffuser: Blown-glass

Flowerpot: PMMA (thermoplastic polymer)

Finish




3706-18 Charcoal grey matte lacquer (ADAPTA RF 9913 WX)



3706-93 White matte lacquer (RAL 9016)

Sketch



Electrical characteristics



VIBIA



Led 2700K CRI >90 2604 lm 93 lm/W

Fixture: 1712.28 lm 49.08 lm/W

Driver included: CC - Constant Current 500 mA 110-240V 50/60Hz

Electronic dimming: 1-10V PUSH

Optional dimming: DALI

Technical characteristics

- Plants not included

Physical characteristics

2 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.2495 m³ /

Gross weight 10.8 kg. / Net weight 7.5 kg.


Installation and assembly

Please see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Efficiency : 1

Coordinate system : CG

Total flux : 1712.28 lm

Maximum value : 66.39 cd/klm

Light position : C=270.00 G=5.00

Symmetry on the planes : Asymmetric

Isolux : Isolux (Floor)

Light position :

X=0.00ft Y=0.00ft Z=8.20ft

Certificates

