

PALMA

Design by Antoni Arola.

VIBIA

Reference

3720.

Application

Hanging lamps

Installation type

Surface

Description

Vibia presents a pendant lamp. It includes two sizes of hand blown glass sphere joined together by a strap and aluminum structures. The intensity of the LED light source is dimmable.

Diffuser

Mat opal triplex blown-glass diffuser

Materials

Profile: Aluminum

Diffuser: Blown-glass

Finish




3720-18 Matt graphite lacquer (ADAPTA RF 9913 WX)



3720-93 Matt white lacquer (RAL 9016)

Sketch



Electrical characteristics



Led 2700K CRI >90 868 lm 93 lm/W

Fixture: 576.51 lm 49.57 lm/W

Driver included: CC - Constant Current 500 mA 110-240V 50/60Hz

Electronic dimming 1-10V PUSH

ficha.fichatecnicaproducto.regulacion.opcional DALI

Physical characteristics

1 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.0460 m³ /

Gross weight 4.0 kg. / Net weight 2.8 kg.


Installation and assembly

Please, see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Efficiency : 1

Coordinate system : CG

Total flux : 576.51 lm

Maximum value : 67.81 cd/klm

Light position : C=0.00 G=0.00

Symmetry on the planes : Double symmetrical

Isolux : Isolux (Floor)

Light position :

X=0.00m Y=0.00m Z=2.50m

Certificates

