

# LINK

Design by Ramón Esteve.

## Reference

**5388.**

## Application

Ceiling Lamps

## Installation type

Surface

## Description

Geometry as decor... The Link is a series of preconfigured geometric patterns that can be arranged across the canvas of a ceiling. These configurations have shallow profiles making them ideal for residential and hospitality settings or anywhere with low ceilings. The combinations of different rectangular shapes create surface fixtures of different sizes, with up to five combined cubist forms.

## Diffuser

Methacrylate diffuser

## Materials

Box: Polyurethane  
Diffuser: Methacrylate

## Finish




**5388-03** Shiny white lacquer (RAL 9010)



**5388-18** Shiny graphite lacquer (RAL 7016)

## Sketch



## Electrical characteristics

8 x 2G11 230V 24W

AND

4 x 2G11 230V 18W



Total 264.0 W

A

# VIBIA



**Fixture:** 3901 lm 15 lm/W

**Driver included:** CV - Contant Voltage 230V 50Hz

**Electronic dimming** DALI PUSH

## Technical characteristics

- Dimmable electronic ballast DALI System and Push.

## Physical characteristics

1 Box / 0.50 x 0.77 x 0.77 m. / Vol. 0.2964 m<sup>3</sup> /

Gross weight 19.5 kg. / Net weight 17.6 kg.

## Installation and assembly

Please, see the installation manual

## Light distribution

### General lighting

Lamp for general lighting that equally distributes the light in all directions.



## Photometric data

Efficiency : 20.32%

Coordinate system : CG

Total flux : 19200.00 lm

Maximum value : 64.68 cd/klm

Light position : C=0.00 G=0.00

Symmetry on the planes : Double symmetrical

Isolux : Floor

Light position :

X=0.00m Y=0.00m Z=3.00m

