PUCK WALL ART

Design by Jordi Vilardell.



Reference

5460.

Application

Wall Lamps

Installation type

Surface

Description

Puck Wall Art is comprised of two disks to create a warm, visually sharp and mathematically creative effect. There are two sizes of disks, allowing the designer to play with varied combinations of indirect light. The resulting design comprises a set of highly dynamic, sculptural compositions, whose shapes emit a cozy light, without casting heavy shadows or a harsh glare.

Diffuser

Methacrylate diffuser

Materials Shade: ABS

Diffuser: Methacrylate

Finish





5460-14 Dark brown lacquer (RAL 8019)

5460-08 Orange lacquer (Pantone 1495M)

Sketch



Electrical characteristics

1 x 2GX13 230V 22W (T5C)

Total 22.0 W



0





Fixture: 683 lm 31 lm/W

Driver included: CV - Contant Voltage 230V 50Hz

Technical characteristics

- A maximum of 40 modules can be connected to a single connection point. For bigger compositions, check connection system.

Physical characteristics

1 Box / 0.26 x 0.51 x 0.51 m. / Vol. 0.0676 m³ / Gross weight 3.7 kg. / Net weight 3.3 kg.

Installation and assembly

Please, see the installation manual

Light distribution

General lighting


Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Efficiency: 37.97% Isolux : Floor Coordinate system : CG Light position: Total flux : 1800.00 lm X=0.00m Y=0.00m Z=3.00m

Maximum value : 65.01 cd/klm Light position: C=75.00 G=145.00 Symmetry on the planes : Double symmetrical



Certificates





