## **PUCK WALL ART**

Design by Jordi Vilardell.



Reference

5461.

Application

Wall Lamps

Installation type

Surface

## Description

Puck Wall Art is comprised of two disks to create a warm, visually sharp and mathematically creative effect. There are two sizes of disks, allowing the designer to play with varied combinations of indirect light. The resulting design comprises a set of highly dynamic, sculptural compositions, whose shapes emit a cozy light, without casting heavy shadows or a harsh glare.

Diffuser

Methacrylate diffuser

Materials Shade: ABS

Diffuser: Methacrylate

Finish



**5461-03** Matt white lacquer (RAL 9010)



**5461-08** Orange lacquer (Pantone 1495M)



**5461-14** Dark brown lacquer (RAL 8019)

Sketch



**Electrical characteristics** 

1 x 2GX13 230V 22W (T5C)

Total 22.0 W



0





**Fixture:** 588 lm 27 lm/W

Driver included: CV - Contant Voltage 230V 50Hz

Technical characteristics

- A maximum of 40 modules can be connected to a single connection point. For bigger compositions, check connection system.

**Physical characteristics** 

1 Box / 0.25 x 0.42 x 0.42 m. / Vol. 0.0441 m<sup>3</sup> / Gross weight 2.9 kg. / Net weight 2.6 kg.

Installation and assembly

Please, see the installation manual

**Light distribution** 

## **General lighting**

Lamp for general lighting that equally distributes the light in all directions.




Photometric data

Efficiency: 32.67% Isolux : Floor Coordinate system : CG Light position:

Total flux : 1800.00 lm X=0.00m Y=0.00m Z=3.00m Maximum value : 59.35 cd/klm

Light position: C=60.00 G=145.00 Symmetry on the planes : Double symmetrical



Certificates





