## **PUCK WALL ART**

Design by Jordi Vilardell.



Reference

5464.

Application

Wall Lamps

Installation type

Surface

## Description

Puck Wall Art is comprised of two disks to create a warm, visually sharp and mathematically creative effect. There are two sizes of disks, allowing the designer to play with varied combinations of indirect light. The resulting design comprises a set of highly dynamic, sculptural compositions, whose shapes emit a cozy light, without casting heavy shadows or a harsh glare.

Diffuser

Methacrylate diffuser

Materials Shade: ABS

Diffuser: Methacrylate

Finish



5464-03 Matt white lacquer (RAL 9010)




**5464-08** Orange lacquer (Pantone 1495M)



**5464-14** Dark brown lacquer (RAL 8019)

Sketch



**Electrical characteristics** 

2 x 2GX13 230V 22W (T5C) 0

Total 44.0 W









**Fixture:** 1267 lm 29 lm/W

Driver included: CV - Contant Voltage 230V 50Hz

Technical characteristics

- A maximum of 40 modules can be connected to a single connection point. For bigger compositions, check connection system.

**Physical characteristics** 

1 Box / 0.43 x 0.51 x 0.51 m. / Vol. 0.1118 m<sup>3</sup> / Gross weight 6.8 kg. / Net weight 5.5 kg.

Installation and assembly

Please, see the installation manual

**Light distribution** 

## **Indirect lighting**

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.

Isolux: Ceiling




Photometric data

Efficiency: 35.20% Coordinate system : CG Total flux : 3600.00 lm

Light position : X=0.00m Y=0.00m Z=2.00m Maximum value : 68.12 cd/klm

Light position: C=280.00 G=150.00 Symmetry on the planes : Asymmetric



Certificates





