

NORTH

Design by Arik Levy.

Reference

5666.

Application

Floor Lamps

Installation type

Surface

Description

Vibia presents a floor lamp. Suspended from the ceiling via an almost invisible steel cable, the light is equipped with a counterweight placed on the ground that guides the electrical cable and allows the stem and the aluminum shade to be placed wherever required.

Diffuser

Methacrylate diffuser

Materials

Cane: Carbon fiber

Shade: Aluminum

Base: Aluminum

Diffuser: PMMA

Finish



5666-04 Matt graphite lacquer (NCS S8500N)



5666-05 Matt blue lacquer (NCS 3040-B10G)




5666-58 Matt cream lacquer (NCS S 2005-Y20R)



5666-93 Matt white lacquer (NCS S 0502-Y)

Sketch



Electrical characteristics

1 x LED 9W 350mA

Total 9.0 W



Led 2700K CRI >80 1041 lm 116 lm/W

Fixture: 766.49 lm 85.17 lm/W

Driver included: CC - Constant Current 350 mA 110-240V 50/60Hz

Electronic dimming PUSH

Technical characteristics

- Accesorio incluido: caja conexión con Driver y Pulsador

Physical characteristics

2 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.0464 m³ /

Gross weight 6.2 kg. / Net weight 4.1 kg.


Installation and assembly

Please, see the installation manual

Light distribution

General lighting - opaque shade

Lamp for general lighting with an opaque shade and distributing light upwards and/or downwards mainly.



Photometric data

Efficiency : 1

Coordinate system : CG

Total flux : 766.49 lm

Maximum value : 423.70 cd

Light position : C=0.00 G=0.00

Symmetry on the planes : Double symmetrical

Isolux : Isolux (Floor)

Light position :

X=0.00m Y=0.00m Z=2.50m

Certificates



